

# ELECTRICAL ACCESSORIES

A comprehensive range of electrical accessories are offered:

H07RN-F **rubber cable** is supplied by the metre in nominal section sizes of 1.5mm<sup>2</sup> to 10.0mm<sup>2</sup>. Also available is 2.5mm<sup>2</sup> individually screened cable (IDS) for mines and quarry use.


A range of **plugs** are available for domestic, site and industrial connections. In particular the **euro converter** is offered which will convert a non-earthed, two pin, europlug into a fused plug. Simply insert the europlug into the converter, snap shut the cover and secure with two screws. Then fit a fuse (supplied) that is rated for the intended appliance. This can only be used with CEE 7 shuko plugs. This product is approved to BS5733, BS1363 plug/socket features and BS1362 fuse link. Approved by BSI and complies with RoHS standards.

Two types of cable joint are offered. The **re-wireable** type is designed to fit cable from 0.75mm<sup>2</sup> to 1.5mm<sup>2</sup> and has IP55 protection. The internal screw terminals enable wires to be connected, or disconnected, easily without the need for special tools and the positive keyway prevents mis-assembly. The collar mechanism allows quick connection or release. The **epoxy** type is designed to fit cable from 0.5mm<sup>2</sup> to 4.0mm<sup>2</sup> and has IP68 protection. This is supplied with joint sleeve, joint cap, crimp connectors and epoxy resin, which requires 12 hours to set. This is a permanent connection.


## CABLE PLUGS JOINTS

ELECTRICAL ACCESSORIES

- ✓ Domestic
- ✓ Commercial
- ✓ Industrial
- ✓ Mines & Quarries
- rubber
- IDS
- 110v
- 230v
- 400v



Rubber 3 Core



Rubber 4 Core



IDS



IDS



110v 16amp




230v 16amp



230v 13amp



Euro Converter



### Epoxy connector



type	voltage	amp	pins	protection
plug	110	16	3	IP44
plug	230	3,5,10 or 13*	3	-
plug	230	16	3	IP44

\* please specify at time of ordering

### Re-wireable connector



voltage	type	to fit nominal section (mm <sup>2</sup> )	protection
230	re-wireable	0.75 - 1.5	IP55
110-230-400	epoxy	0.5 - 4.0	IP68

voltage	type	amp	pins	protection
230	euro converter	3,5,10 or 13	3	-

\* please specify at time of ordering

no. of cores	type	nominal section (mm <sup>2</sup> )	unit
3	rubber	1.5	metre
3	rubber	2.5	metre
3	rubber	4.0	metre
3	rubber	6.0	metre
3	rubber	10.0	metre
4	rubber	1.5	metre
4	rubber	2.5	metre
4	rubber	4.0	metre
4	rubber	6.0	metre
4	rubber	10.0	metre
3	IDS	2.5	metre